

SKYMAX SERIES

RM - 685-705W - 210M/132TB

N-TOPCon

Bifacial Monocrystalline Module

MANUFACTURED BY RONMA SOLAR.

2384×1303×33

Dimensions (mm)

132 CELL

Dimensions (mm)

1500V DC

Max. system voltage

182×91

Cell size (mm)

685-705Wp

Power output

22.70%

Max. efficiency

Light Redirecting Film

Light Redirecting Film technology ensure the bifaciality and reliability of the module, effectively increasing the power performance.


Non-Destructive (NDC) Cutting Tech

The cutting surface is smooth, avoiding the loss of the cells' mechanical structure and ensuring sufficient current.

Junction Box Laser Welding Tech

The laser's high energy density and precise positioning control allow it to accurately manage the junction box's welding position and timing, ensuring high-quality welding and reliability, thereby enhancing module safety.

Linear Performance Warranty



15-year product warranty / 30-year linear power warranty



POLESTAR ENERGY S.L.


www.polestarenergy.es

Calle Alcalá 87, 3º Izq. 28009 Madrid


+34 682 421 164

comercial@polestarenergy.es


Dimensions of PV Module



RM-705W-210M/132TB
I-V characteristics at different irradiances
Cells temp.=25°C



I-V characteristics at different temperatures



ELECTRICAL CHARACTERISTICS (STC*)

Rated Power in Watts-Pmax (Wp)	685	690	695	700	705
Open Circuit Voltage-Voc (V)	47.10	47.90	48.30	48.60	48.80
Short Circuit Current-Isc (A)	18.21	18.25	18.28	18.32	18.36
Max. Power Voltage-Vmpp (V)	39.80	40.10	40.30	40.50	40.70
Max. Power Current-Impp (A)	17.19	17.23	17.25	17.29	17.33
Module Efficiency (%)	22.05	22.21	22.37	22.53	22.70
Maximum system voltage	1500V DC				
Fuse Rating(A)	30				
Temperature coefficient Pmax	-0.30%/°C				
Temperature coefficient Isc	0.046%/°C				
Temperature coefficient Voc	-0.25%/°C				

*STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

WORKING CHARACTERISTICS (NOCT*)

Rated Power in Watts-Pmax (Wp)	521	526	530	534	538
Open Circuit Voltage-Voc (V)	37.30	37.70	37.80	38.00	38.20
Short Circuit Current-Isc (A)	13.94	13.96	14.02	14.05	14.08
Max. Power Voltage-Vmpp (V)	45.20	45.40	45.80	46.00	46.20
Max. Power Current-Impp (A)	14.67	14.71	14.73	14.76	14.80
Power tolerance	0~+3%				
NOCT	45°C±2°C				
Operating Temperature	-40°C~85°C				

*NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Electrical characteristics with different rear side power gain

	Pmax(Wp)	Voc/V	Isc/A	Vmpp/V	Imp/A
5%	766	49.80	19.49	41.70	18.40
10%	803	49.80	20.42	41.70	19.27

The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle, etc.) and albedo of the ground.

MECHANICAL CHARACTERISTICS

Number of cells	132pcs	Type of frame	Anodized Aluminum Alloy
Size of cell (mm)	182×91	Size of module (mm)	2384×1303×33
Type of cell	N-TOPCon Mono	Weight (kg)	38
Thickness of glass (mm)	2.0	Cables/connectors	4.0mm², MC4 compatible
Junction box	IP68, 1500V DC, 3 Diodes	Length of Cable	+300mm/-200mm (connector inc.)

PACKAGING CONFIGURATION

Height of Modules (mm)	33
Number of Modules Per Pallet	33
Packaging Box Dimensions (l×w×h) (mm)	1326×1140×2515
Box Gross Weight (kg)	1280
Number of Modules Per 40ft (HQ) Container	594
Number of Pallets Per 40ft (HQ) Container	18

Notes: Read safety and installation instructions before using the product. The data provided in this data sheet are subject to change without notice.