

SKYMAX SERIES

RM-485-500W- 187R/120TB

N-TOPCon

Full Black Bifacial Monocrystalline Module

MANUFACTURED BY RONMA SOLAR.

1950×1134×35

Dimensions (mm)

120 CELL

Dimensions (mm)

1500V DC

Max. system voltage

182×91

Cell size (mm)

485-500Wp

Power output

22.61%

Max. efficiency



Higher Power Output

Module power increases by 5-25% generally, bringing significantly lower LCOE and higher IRR. 0-5w positive tolerance output warranty.



Multi Busbar Technology

By improving optical utilization rate, power increases by 2~3% and efficiency increases by 0.4~0.6%.



PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and material control.



Low-light Performance

Excellent performance in low light.




Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance certified by TUV NORD.




EL Full Inspection

Dual-stage 100% EL Inspection.



Linear Performance Warranty



12-year product warranty / 30-year linear power warranty

Product and Systems Certificates

IEC61215/IEC61730/IEC61701/IEC62716/WEEE De93315506



POLESTAR ENERGY S.L.


www.polestarenergy.es

Calle Alcalá 87, 3º Izq. 28009 Madrid

+34 682 421 164


comercial@polestarenergy.es

Dimensions of PV Module




RM-500W-187R-120TB

I-V characteristics at different irradiances



I-V characteristics at different temperatures



ELECTRICAL CHARACTERISTICS (STC*)

Rated Power in Watts-Pmax (Wp)	485	490	495	500
Open Circuit Voltage-Voc (V)	43.62	43.82	44.02	44.22
Short Circuit Current-Isc (A)	13.86	13.92	13.98	14.04
Max. Power Voltage-Vmpp (V)	36.27	36.47	36.67	36.87
Max. Power Current-Impp (A)	13.38	13.44	13.50	13.56
Module Efficiency (%)	21.93	22.16	22.39	22.61
Maximum system voltage	1500V DC			
Fuse Rating(A)	25			
Temperature coefficient Pmax	-0.29%/°C			
Temperature coefficient Isc	0.045%/°C			
Temperature coefficient Voc	-0.25%/°C			

*STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

WORKING CHARACTERISTICS (NOCT*)

Rated Power in Watts-Pmax (Wp)	365	369	373	376
Open Circuit Voltage-Voc (V)	41.28	41.47	41.65	41.84
Short Circuit Current-Isc (A)	11.16	11.21	11.26	11.31
Max. Power Voltage-Vmpp (V)	33.88	34.07	34.25	34.44
Max. Power Current-Impp (A)	10.80	10.85	10.90	10.95
Power tolerance	0~+3%			
NOCT	45°C±2°C			
Operating Temperature	-40°C~85°C			

*NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Electrical characteristics with different rear side power gain

	Pmax(Wp)	Voc/V	Isc/A	Vmpp/V	Impp/A
5%	458	41.09	14.49	33.88	13.95
10%	479	41.09	15.18	33.88	14.62

The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle, etc.) and albedo of the ground.

MECHANICAL CHARACTERISTICS

Number of cells	120pcs	Type of frame	Anodized Aluminum Alloy
Size of cell (mm)	182×91	Size of module (mm)	1950×1134×35
Type of cell	N-TOPCon Mono	Weight (kg)	22.7
Thickness of glass (mm)	2.0	Cables/connectors	4.0mm², MC4 compatible
Junction box	IP68, 1500V DC, 3 Diodes	Length of Cable	+300mm/-200mm (connector inc.)

PACKAGING CONFIGURATION

Height of Modules (mm)	35
Number of Modules Per Pallet	31
Packaging Box Dimensions (l×w×h) (mm)	1800×1140×1260
Box Gross Weight (kg)	808
Number of Modules Per 40ft (HQ) Container	806
Number of Pallets Per 40ft (HQ) Container	2026

Notes: Read safety and installation instructions before using the product. The data provided in this data sheet are subject to change without notice.

POLESTAR ENERGY S.L.

www.polestarenergy.es

Calle Alcalá 87, 3º Izq. 28009 Madrid

+34 682 421 164

comercial@polestarenergy.es

