

SE WOOD W155

Water-repellent, breathable for natural wood.

PRODUCT DESCRIPTION:

- SE WOOD W 155 is a breathable water-repellent solution designed for natural wood.
- It is a hydroalcoholic solution with a high concentration of silanes, formulated for the water-repellent treatment of untreated natural woods such as chestnut, cedar, ash, larch, walnut, olive, oak, teak, and more.
- The treatment provides the wood surface with an excellent breathable water-repellent effect, facilitating cleaning through its "anti-adhesive" properties.



CHEMICAL-PHYSICAL CHARACTERISTICS

Appearance	Transparent liquid
Density	Approx. 1
pH	5
Solvents	Water/IPA mixture

PRODUCT APPLICATION

Usage conditions	• SE WOOD W 155 is a new breathable, transparent water-repellent product that is ready to use without forming a surface film. It penetrates deeply by impregnation into the substrate, providing an excellent beading effect while maintaining the wood's original appearance. The product should be applied to a clean, untreated surface (freshwater washing is recommended). If the surface has been previously treated, sanding is required to remove treatment residues.
Application Conditions	• Apply SE WOOD W 155 to surfaces that are not hot or exposed to direct sunlight, allowing the product time to penetrate deeply. • The treatment can be applied with a brush or roller in a single coat or multiple coats, wet-on-wet. After application, the treated surface should be left to dry at room temperature for at least 24 hours. • For recreational boats, SE WOOD W 155 can be applied by immersion or spraying on sails, or by spraying, brush, or roller on a single or multiple wet-on-wet coats for the canopy and teak deck. The treated surface should be left to dry at room temperature for at least 24 hours after treatment.

PERFORMANCE

The performance of SE WOOD W 155 depends on the nature and porosity of the surface to be treated and the number of coats applied. For wood treated with one coat, the average consumption is approximately 100 g/m²

PACKAGING AND STORAGE

Storage: Store the product at temperatures between +5°C and +35°C, and protect it from heat and open flames.

Packaging: Available in 50 L and 200 L drums.

PROPERTIES

Excellent water-repellent effect
Breathable coating
Transparent, film-free finish
Maintains the original appearance of the wood

PRECAUTIONS

Avoid contact with heat and flames. For additional safety information, refer to the safety data sheet.

The information contained in this document is based on trials carried out by our Technical centres and data selected from literature, but shall in no event be held or constitute or imply any warranty or undertaking, expressed or implied, or commitment on our part. Our formal specifications define the limit of our commitment. No liability what so ever can be accepted by SEIRE with regard to the handling, processing or use of the product or products concerned which must in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.