

Gotion GRID 5015

Liquid-Cooled Energy Storage System III



- 5015kWh**
High Energy
- 12,000 Cycles**
Long Life Span
- 3-Layer Protection**
High Safety
- 20ft**
Standard Container
- 3°C**
Intelligent Temperature Control
- 600MWh per acre**
Optimized Energy Density
- ✓ **High-Energy-Density System**
- ✓ **Optional Battery Container**
- ✓ **Optimal Space Utilization**
- ✓ **Integrated BMS**
- ✓ **Low Cost with Minimal Footprint**

>>> ESS Product Solution

- Thermal Energy Storage
- Wind and Solar Energy Storage
- Shared Energy Storage
- Peak-valley Arbitrage

System-5015

*Rack×12

Pack×48

Cell×4992

314Ah

*The image illustrates two electrical racks physically mounted together to fit into the container, and one electrical rack comprises four battery packs connected in series.

Electrical Parameters

Cell Type	LFP-314Ah
Cell Cycle Life	> 12,000*
Rated Voltage of Single Cell	3.2Vdc
Pack Configuration	1P104S
Rack Configuration	1P416S
System Configuration	12P416S
System Nominal Energy	5015kWh
System Rated Voltage	1331.2Vdc
System Voltage Range	1040Vdc ~ 1497.6Vdc
Charge / Discharge Rate	≤0.5p @ 25°C/77°F

Components

High Voltage Box	Integrated
Confluence Cabinet	Integrated
Monitoring System (HMI)	Integrated
Fire Suppression System	<ul style="list-style-type: none"> • Explosion-proof Exhaust and Ventilation System • Temperature/Smoke/Combustible Gas Detection System • PACK-level submerged Fire Extinguishing System • Aerosol Fire Extinguishing System • Prefabricated Water Sprinkler System (Optional)
Thermal Management System	<ul style="list-style-type: none"> • Integrated Liquid Cooler 60kW Cooling Capacity for Battery • Air-cooling for Other Equipment
EMS	Not Integrated
BMS	Integrated Option: U.S. Manufactured

Conditions

Storage Temperature	-30°C ~ 60°C / -22°F ~ 140°F
Working Ambient Temperature	-30°C ~ 45°C / -22°F ~ 113°F (>45°C/113°F Derating)
Working Relative Humidity	0% ~ 95% (Non-condensing)
Working Altitude	≤3000m/9842ft (>3000m/9842ft Derating)

Other Parameters

Ingress Protection	IP55 (Except Liquid Cooler)
Communication Interface	CAN, RS-485, Ethernet
Communication Protocol	CAN, Modbus-TCP/IP, Modbus RTU, IEC104
Dimensions (W×D×H)	6058mm×2438mm×2896mm/238.5in×96in×114in (20ft Container)
Weight (t)	44
Standards & Certification	UL9540A, UL9540, UL1973, UN38.3, UN3536, NFPA855, NFPA69, RoHS, Reach, (EU) 2023/1542, IEC 62477-1, IEC 60529, IEC 61000-6-2, IEC 61000-6-4, IEC 62933-5-2, IEC 63056, IEC 62619, GB/T 36276

*70% capacity retention after 12,000 cycles (0.5P charge/discharge, 90% DoD at 25±2°C)
© 2024 Gotion High-tech Co., Ltd. All rights reserved. Version 2.0. Partial certifications are in progress.